

## FOLDING SLIDING DOORS ENQUIRY/ORDER FORM

Company: .....

Account No. ....

Address: .....

..... Postcode: .....

Tel: .....

Fax: .....

Contact Name: .....

Email: .....

Requested Delivery Date: .....  
*(Lead time of 10 working days)*

Order Reference: .....

Signature: .....

Page  of

Quote	
Order	

### FOLDING OPTIONS *(When viewed from outside)*

**NB. Minimum sash width 550mm per pane, maximum sash width 1000mm per pane.**

Total number of leaves	Number of leaves folding left	Number of leaves folding right
For Example: <b>3</b> <i>Total number of door leaves</i>	<b>1</b> <i>Number of door leaves opening left</i>	<b>2</b> <i>Number of door leaves opening right</i>

### DIMENSIONS

**Overall width:**  
.....  
*Maximum width: 6000mm*

**Overall height:**  
.....  
*Maximum height: 2400mm*

### EXTERNAL STYLING

<input type="checkbox"/> Pencil Round	
<input type="checkbox"/> Chamfered	
<input type="checkbox"/> Squared	
<input type="checkbox"/> Decorative	

*\*44mm Triple Glazed - Pencil Round only*

### FRAME COLOUR

External:	Internal:
<input type="checkbox"/> White	<input type="checkbox"/> White
<input type="checkbox"/> Cream	<input type="checkbox"/> Cream
<input type="checkbox"/> Grey	<input type="checkbox"/> Grey
<input type="checkbox"/> Black	<input type="checkbox"/> Black

### OPENING IN/OUT

Open in     Open out

### TRICKLE VENTS

Required     Not required

### HARDWARE

Anodised Silver (matt finish)

Anodised Black (matt finish)

Brushed Graphite

*Locks/keeps are Anodised Silver.  
Roller units are Black Anodised powder finish.  
Brushed Graphite uses Anodised Black hinges.*

### SILL TYPE

<input type="checkbox"/> Standard integrated 120mm sill <i>(Outward opening only)</i>	<input type="checkbox"/> Frame - No sill
<input type="checkbox"/> Part M low threshold*	<input type="checkbox"/> Frame - 150mm sill**
<input type="checkbox"/> Part M low threshold ramp/cover*	
<input type="checkbox"/> Part M low threshold ramp/ramp*	

*\*All Silver Anodised Aluminium.  
\*\*Part M low threshold is not compatible with 150mm sill.*

### GLAZING BEAD

Squared/Squared - 28mm  
- 4 Sides

Squared/Chamfered - 28mm  
- Chamfered Verticals

Squared/Squared - 44mm  
- 4 Sides

### GLAZING OPTIONS

*(All Toughened)*

<input type="checkbox"/> Standard double glazed - 28mm (1.5 W/m <sup>2</sup> K U-value*)	<input type="checkbox"/> Triple glazed - 44mm (1.0 W/m <sup>2</sup> K U-value*)
<input type="checkbox"/> Celsius double glazed - 28mm (1.4 W/m <sup>2</sup> K U-value*)	<input type="checkbox"/> Standard double glazed (Laminated) - 28mm (1.5 W/m <sup>2</sup> K U-value*)

*\*Figures quoted are whole door U-values based on BFRC standard bi-fold door*

### SKETCH YOUR DESIGN HERE: *(When viewed from outside)*

Additional notes: .....

.....

.....

**Phone** 01763 271 811  
**Web** www.welglaze.co.uk  
**Email** sales@welglaze.co.uk

## ORDER GUIDELINES

### MAXIMUM AND MINIMUM DOOR SIZES

STYLE	DOOR WIDTHS		DOOR HEIGHTS			
	MINIMUM	MAXIMUM	MINIMUM		MAXIMUM	
			FRAME / INTEG	PART M LT	FRAME / INTEG	PART M LT
220	1500	2126	2020	2000	2400	2400
330	1800	3138	2020	2000	2400	2400
321	1800	3138	2020	2000	2400	2400
440	3000	4150	2020	2000	2400	2400
431	2350	4150	2020	2000	2400	2400
422	3000	4150	2020	2000	2400	2400
550	2925	5162	2020	2000	2400	2400
541	2925	5162	2020	2000	2400	2400
532	2925	5162	2020	2000	2400	2400
660	4500	6000	2020	2000	2400	2400
651	3475	6000	2020	2000	2400	2400
642	4500	6000	2020	2000	2400	2400
633	3475	6000	2020	2000	2400	2400
770	4050	6000	2020	2000	2400	2400
761	4050	6000	2020	2000	2400	2400
752	4050	6000	2020	2000	2400	2400
743	4050	6000	2020	2000	2400	2400

*NB: Heights noted do not include additional thermally broken sill.  
Allow 26.5mm for this if it is required.*